

## Máy in mã vạch Godex G530



GoDEX G530 - Thiết kế mạnh mẽ và bền bỉ lâu dài - Sử dụng ribbon 300m - Công nghệ "Twin-sensor" - Hỗ trợ giao diện có sẵn bao gồm: - usb2.0, serial và Ethernet - Usb2.0 và Parallel - Độ phân giải: 300dpi

Ảnh giá: Chưa có ảnh giá

### Price

5,990,000 ?

1,153,135 ?-

[Hỏi về sản phẩm này](#)

### Description

#### GoDEX G530

- Sử dụng ribbon 300m

- Công nghệ "Twin-sensor"

- Hỗ trợ giao diện có sẵn bao gồm:

- usb2.0, serial và Ethernet

- Usb2.0 và Parallel

Thiết kế mạnh mẽ và bền bỉ lâu dài

- Độ phân giải: 300dpi

**Thông tin chung:**

G530 lý tưởng cho các loại in mã vạch in nhũ:

- Sản phẩm nhũ, serial, theo dõi tài sản, in nhãn hàng s? d?ng, túi, ?? trang s?c, v?i...

**Thông số kỹ thuật:**

Thông số kỹ thuật:

- Truy cập nhũ/ nhũ? t?c? p
- ?? phân giải: 300dpi( 12dots/mm)
- Tốc độ in: 4ips ( 102mm/s)
- Chiều rộng khay in: 4.16"( 105.7mm)
- Chiều cao nhãn in: min 0.16"(4mm), max 68"( 1727mm)
- Bộ nhớ: 4MB Flash( 2MB s? d?ng l?u tr? ) /16MBSDram
- Sensor: sensor?i?u ch?nh. sensorc? ??nh
- Ribbon: Wax, wax/resin, resin( 300m)

**Thông số chi tiết**

Print Method	Thermal Transfer / Direct Thermal
Resolution	300 dpi (12 dots/mm)
Print Speed	4IPS (102 mm/s)
Print Width	4.16" (105.7 mm)
Print Length	Min. 0.16" (4 mm)**; Max. 30" (762 mm)
Processor	32 Bit RISC CPU
Memory	8MB Flash (4MB for user storage) / 16MB SDRAM
Sensor Type	Adjustable reflective sensor. Fixed transmissive sensor, central aligned
Media	Types: Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming Width: 1" (25.4 mm) Min. - 4.64" (118 mm) Max. Thickness: 0.0024" (0.06 mm) Min. - 0.01" (0.25 mm) Max. Label roll diameter: Max. 5" (127 mm) Core diameter: 1", 1.5", 3" (25.4 mm, 38.1 mm, 76.2 mm)
Ribbon	Types: Wax, wax/resin, resin Length: 981' (300 m) Width: 1.18" Min - 4.33" (30 mm - 110 mm) Max Ribbon roll diameter.: 2.67" (68 mm) Core diameter: 1" (25.4 mm)
Printer Language Software	EZPL, GEPL, GZPL auto switch Label design software: GoLabel (for EZPL only) Driver: MAC , Linux Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 DLL: Win CE , .NET , Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 / Android
Resident Fonts	Bitmap fonts: 6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical directions TTF fonts?CG Triumvirate™ (Bold / Italic / Underline). 0°, 90°, 180°, 270° rotatable
Download Fonts	Bitmap fonts: 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Asian fonts: 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese (S-JIS), Korean (KS-X1001)90°,180°,270°, rotatable and 8 times expandable in horizontal and vertical directions TTF fonts: 90°, 180°, 270° rotatable
Barcodes	1-D Bar codes: Code 39, Code 93, EAN 8/13 (add on 2 & 5), UPC A/E (add on 2 & 5), I 2 of 5 & I 2 of 5 with Shipping Bearer Bars, Codabar, Code 128 (subset A, B, C), EAN 128, RPS 128, UCC 128, UCC/EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar, German Post Code, Planet 11 & 13 digit, Japanese Postnet, I 2 of 5 with human readable check digit, Standard 2 of 5, Industrial 2 of 5 , Logmars, Code 11, Code 49, Cadablock 2-D Bar codes: PDF417, Datamatrix code, MaxiCode, QR code, Micro PDF417, Micro QR code and Aztec code

Code Pages	CODEPAGE 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 WINDOWS 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode UTF8?UTF16BE?UTF16LE
Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software
Interfaces	USB + Parallel Port USB + Serial Port + Ethernet
Control Panel	Two bi-color status-LEDs: Ready, Status Control key: FEED
Power	Auto Switching 100-240VAC, 50-60Hz
Environment	Operation temperature: 41°F to 104°F (5°C to 40°C) Storage temperature: -4°F to 122°F (-20°C to 50°C)
Humidity	Operation: 30-85%, non-condensing. Storage: 10-90%, non-condensing.
Agency Approvals	CE(EMC), FCC Class A, CB, cUL, CCC
Dimension	Length: 11.2" (285 mm) Height: 6.8" (171 mm) Width: 8.9" (226 mm)
Weight	6 lbs (2.72Kg) ,excluding consumables
Options	Cutter Module Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder

**Nh?n xét**

There are yet no reviews for this product.